

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)


PCT

(10) International Publication Number
WO 2004/057234 A1

- (51) International Patent Classification⁷: **F23C 3/00**, F23D 14/76
- (21) International Application Number: PCT/SE2003/001887
- (22) International Filing Date: 4 December 2003 (04.12.2003)
- (25) Filing Language: Swedish
- (26) Publication Language: English
- (30) Priority Data:
0203845-3 23 December 2002 (23.12.2002) SE
- (71) Applicant (for all designated States except US): SAND-
VIK AB [SE/SE]; S-811 81 Sandviken (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): LEWIN, Thomas
[SE/SE]; Bergslagsvägen 227 B, S-734 40 HALLSTA-
HAMMAR (SE).
- (74) Agents: ÖRTENBLAD, Bertil et al.; Noréns Patentbyrå
AB, Box 10198, S-100 55 Stockholm (SE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AT A GAS BURNER AND A COMBINED GAS BURNER AND COOLER



(57) Abstract: The present invention relates to a method relating to the operation of a burner and/or cooler (3), wherein gases are caused to flow through an inner pipe (7), out into an outer pipe (5) which surrounds the inner pipe (7), and back through that part of the volume of the outer pipe (5) not accommodated by the volume of the inner pipe (7). The invention is characterised by placing an inner bottom plates (8) in the outer pipe (5) in spaced relationship with the closed bottom (9) of said outer pipe (5), whereby the gases flowing through the inner pipe (7) and out into the outer pipe (5) are caused to turn back and pass between the outer pipe (5) and the inner pipe (7), thereby creating a gas pocket (12) between the bottom (9) of said outer pipe (5) and the bottom plate (8).

WO 2004/057234 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.